

Docket # 70471

RIDE APPARATUS

FIELD OF THE INVENTION

This invention relates to ride apparatus and particularly (but not exclusively) to ride apparatus used in amusement parks and the like.

BACKGROUND OF THE INVENTION

5 A variety of amusement rides is known for use in amusement parks. Such rides typically comprise dodgem, log flume, roller coaster and vertical drop rides. However, these rides are commonplace and there is an increasing demand for new, novel rides to maintain interest in said parks.

SUMMARY OF THE INVENTION

Accordingly, the present invention provides an amusement ride comprising an output member having an anthropomorphic robot arm adapted for six degrees of movement, said ride further comprising a passenger station in moveable engagement with said output member, a platform, and optionally a ticket reader.

The amusement ride is preferably supported on the ground. Alternatively, the amusement ride may be supported from a wall or from a ceiling.

More preferably, the ride may be mounted on a carousel. Alternatively, the ride may be mounted on a column. The column may be provided with means to cause vertical movement of the ride along a path parallel to the axis of the column. Alternatively, the ride may be mounted on a column which is in turn mounted on a carousel.

The passenger station preferably comprises one or more seats.

The passenger station preferably has means for audio-visual interaction. The audio-visual interaction may be respectively provided by speakers and a display means.

The visual and audio interaction may, separately or together, be synchronized with movements of the ride.

The audio and visual interaction data is stored on a data carrier. The data carrier may be a Mini Disc (MD), a CD-ROM, a magneto-optical device, a video tape, a hard drive, a Digital Versatile Disc (DVD) or other equivalent data carrier. The audio and visual interaction data may be stored on a combination of any two or more of the aforementioned data carriers.

Lighting effects may be used throughout the audio-visual interaction. The lighting

effects may be synchronized with the ride. The lighting effects may comprise, for example, strobe, laser or disco light shows or any combination thereof.

The display means may be a plasma screen, a liquid crystal display, an active matrix Organic Light Emitting Diode (OLED) display, or a Light Emitting Polymer (LEP) display.

5 The visual interaction may alternatively be provided by a projector and screen.

The seats preferably comprise retaining means to retain a passenger when the ride is operable.

The retaining means may comprise a belt, for example, a safety belt or a pull down rigid harness or similar harness. Alternatively, the retaining means may comprise a cage.

The retaining means is preferably in operative engagement with a linear actuator.

10 The amusement ride may further comprise a weight sensor, said weight sensor providing a means to counter out of balance loads. Alternatively, the weight sensor provides a means to counter a maximum weight overload.

The amusement ride may further comprise a controller. The controller is preferably located in the passenger station. Alternatively, the controller is located at a passenger entrance
15 to the ride.

The controller may be used to select a pre-programmed ride. Alternatively, the controller may be used to control the amusement ride independently of the pre-programmed ride.

20 The controller is preferably a joystick. Alternatively, the controller may be a steering wheel or a joypad.

The controller may further comprise one or more foot pedals.

The controller may comprise a combination of the aforementioned joystick and/or steering wheel and/or joypad and/or foot pedals.

The ticket reader can read a ticket, said ticket preferably being compatible with said ride. The ticket may be a card made of a plastics material. The ticket preferably has a code
5 defining a pre-programmed ride. The code is preferably a bar code. Alternatively, the code may be contained in a microchip incorporated in the ticket.

The platform preferably comprises one or more steps, with a raised platform in operative engagement with said steps. The platform, in use, may suitably be adapted for pivotal movement about a substantially horizontal axis.

10 The platform is preferably raised and lowered about its axis by means of an actuator. The actuator may be hydraulically or pneumatically operated. The platform may be raised or lowered about its axis by a combination of hydraulic or pneumatic actuators.

Alternatively, the platform may be fixed and the amusement ride may be adapted to be lowered to a position which allows the ingress and egress of passengers respectively on to or
15 off from the amusement ride.

In a further alternative the platform may be retracted into a stowage compartment and, in use, said platform is extended from the stowage compartment to engage with the ride in a lowered position.

20 The platform may be retracted and extended by means of one or more actuators. The actuators may be hydraulically or pneumatically operated, or a combination of hydraulic and pneumatic operation.

The platform preferably further comprises a safety barrier. The safety barrier, in use, may suitably be adapted for pivotal movement about a substantially vertical axis. Alternatively, the platform and safety barrier may each be adapted for pivotal movement about a substantially 45° axis (relative to the ground).

5 The safety barrier is preferably operated about its axis by means of an actuator. The actuator may be hydraulically or pneumatically operated.

The amusement ride preferably further comprises safety means. Preferably the safety means is controlled by a computer.

10 Preferably the safety means comprises actuators. The actuators may be electro-mechanically, hydraulically or pneumatically operated, or a combination of electro-mechanical, hydraulic and pneumatic operation.

The safety means preferably limits a G-force generated by the amusement ride.

15 The amusement ride may comprise more than one of said rides. Where two or more rides are employed they may be programmed to move synchronously. Alternatively, it may be programmed to move asynchronously. Two or more rides may be used in a combat game.

The ride may be water-proofed for use in a "splash park".

The ride may comprise water cannons for use in a combat-type game in a splash park.

20 The various features of novelty which characterize the invention are pointed out with particularity in the claims annexed to and forming a part of this disclosure. For a better understanding of the invention, its operating advantages and specific objects attained by its uses, reference is made to the accompanying drawings and descriptive matter in which preferred

embodiments of the invention are illustrated.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings:

Figure 1 is a perspective view showing an amusement ride output member in accordance with
5 the present invention;

Figure 2A is a side view of the amusement ride of Figure 1 in an operative condition during a ride;

Figure 2B is a side view of the amusement ride of Figure 1 in another operative condition during a ride;

10 Figure 2C is a side view of the amusement ride of Figure 1 in another operative condition during a ride;

Figure 2D is a side view of the amusement ride of Figure 1 in another operative condition during a ride;

15 Figure 2E is a side view of the amusement ride of Figure 1 in another operative condition during a ride;

Figure 2F is a top view of the amusement ride of Figure 1 in another operative condition during a ride;

Figure 3A is a side view of the amusement ride of Figure 1 in an alternative mounted condition;

20 Figure 3B is a side view of the amusement ride of Figure 1 in another alternative mounted condition;

Figure 4 is a perspective view showing two amusement rides of Figure 1 in a combat game;

Figure 5A is a side view showing a passenger station in accordance with the present invention;

Figure 5B is a perspective view showing a passenger station in accordance with the present invention;

5 Figure 5C is a side view showing a passenger station in accordance with the present invention;

Figure 6A is a side view showing a part of a first procedure for vacating the amusement ride;

Figure 6B is a side view showing another part of a first procedure for vacating the amusement ride;

10 Figure 6C is a side view showing another part of a first procedure for vacating the amusement ride;

Figure 7A is a side view showing a part of a second procedure for vacating the amusement ride;

Figure 7B is a side view showing another part of a second procedure for vacating the amusement ride;

15 Figure 7C is a side view showing another part of a second procedure for vacating the amusement ride;

Figure 8A is a side view showing a part of a third procedure for vacating the amusement ride;

Figure 8B is a side view showing another part of a third procedure for vacating the amusement ride;

20 Figure 8C is a side view showing another part of a third procedure for vacating the amusement ride;

Figure 9A is a side view showing the use of linear actuators or safety interlocks in the operation

of a retaining means;

Figure 9B is a side view showing the use of linear actuators or safety interlocks in the operation of a retaining means;

Figure 9C is a top view showing the use of linear actuators or safety interlocks in the operation of a retaining means;

Figure 10 is a schematic perspective view showing the ride operatively connected with other rides for synchronous movement;

Figure 11A is a schematic perspective view showing combinations of rides operatively connected in an arrangement;

Figure 11B is a schematic perspective view showing combinations of rides operatively connected in an alternative arrangement;

Figure 11C is a schematic perspective view showing combinations of rides operatively connected in an alternative arrangement;

Figure 11D is a schematic perspective view showing combinations of rides operatively connected in an alternative arrangement;

Figure 12A is a side view showing the ride adapted to be incorporated into a fairground ride, such as a carousel or the like;

Figure 12B is a side view showing the ride adapted to be incorporated into a fairground ride, such as vertical lift, or the like.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to the drawings in particular, Figure 1 shows an amusement ride 1 comprising a base portion 2 supported on the ground and a trunnion 7 mounted on the base portion 2 to give rotation about a substantially vertical axis A. The trunnion 7 is in operative engagement with a first elongate member 4, said elongate member being adapted to move about a substantially horizontal axis B, said elongate member being in operative engagement with a second elongate member 6 adapted to move about a substantially horizontal axis C parallel to axis B. The second elongate member has a further 3 degrees of movement about the axis of said second elongate member 6 and a passenger station 15 in moveable engagement with said member. The amusement ride movements about said axes are controlled by motors 16, 17 and 18.

Figures 2A to 2F illustrate the various conditions that the amusement ride 1 of Figure 1 may assume during a ride. The passenger station 15 is shown having two seats, 20 and 21.

Referring to Figures 3A and 3B, alternative mountings of the amusement ride are illustrated. The ride 1 may be supported from a wall 30 or a ceiling 40. The passenger station may also be configured so that arms and legs of a passenger are unsupported.

Figure 4 shows two amusement rides 1 in use in a combat game. The two rides are diametrically opposed to each other at a predetermined distance X. Said rides are each mounted on a fixed base or (as shown) on a base 50 in sliding engagement with a rail track 51, the bases and the tracks being parallel with each other. The passenger stations 15 are provided with a controller 52 and with optical (e. g. infra-red, photoelectric or laser) emitter and

receiver assemblies 53, enabling the said passenger stations 15 to interact with each other. In a splash park, the optical emitter and receiver assemblies may be substituted with one or more water cannons.

The ride is enclosed by a reticulated fence 44 having a closure 60 (for ingress and egress of passengers) and a ticket machine 61 located adjacent the closure 60, for passengers to buy tickets for said ride.

The combat game is controlled by a computer 70. The computer 70 is integrated with the ticket machine 61 and with the two rides.

Figures 5A and 5B show the passenger station 15. The passenger station 15 is in movable engagement with the output member 80 of the ride. The passenger station 15 comprises a seat 81 with a weight sensor 90 located in the seat 81, a joystick controller 83 and a display means 82.

Figure 5C shows a passenger station 15 fitted with a pull down safety harness 84. The seat 81 is not contained in a capsule 85 (see Figure 5A).

Figures 6A to 6C illustrate an aligning procedure for the ride. The ride 1 is shown in a first operative condition 100, attained at the beginning or end of a ride. The robot then lowers to a second operative condition 101, where an optical emitter 200 and receiver 210 assembly, one of said emitter and receiver being located on the ride, ensure that the ride is in the correct aligned position. One or more optical emitter and receiver assemblies may be used to monitor the aligned procedure. One or more optical emitter and receiver assemblies may be used to monitor a ride throughout a ride sequence. Concomitantly a platform 102, activated by

hydraulics, is raised from a first operative condition 103 to a second operative condition 104 under the ride 1 (which is in a second operative condition 101). The passengers may then leave/enter the ride. Alternatively, the platform 102 is fixed and the ride is located on a vertically moving pedestal 105 as shown in Figures 7A to 7C. The ride is in a first operative condition 100, attained at the beginning or at the end of a ride. The ride then lowers to an intermediate operative condition 107. The pedestal 105 is lowered to a second operative condition 101 bringing the passenger into contact with the fixed platform 102. Again, the aforementioned optical emitter and receiver-assemblies may be used to monitor the aligning procedure. The passengers may then enter or leave the ride 1.

In a further alternative shown in Figures 8A to 8C the ride 1 is in a first operative condition 100, attained at the beginning or at the end of a ride. The robot then lowers to a second operative condition 101, where an optical emitter 200 and receiver 210 assembly, one of said emitter and receiver being located on said ride, to ensure that the ride is in the correct aligning position. One or more optical emitter and receiver assemblies may be used to monitor the aligning procedure. Concomitantly a platform 102 activated by hydraulics is extended from a first retracted condition 103 to a second operative condition 104 to engage with the ride 108. The engagement of the platform with the ride may facilitate part of a safety check for the above aligning procedure.

Upon leaving the ride the retaining means (e.g. a safety belt or cage) must be released. Figures 9A to 9C illustrate the use of shot bolt actuators 110 in releasing the retaining means. The shot bolt actuators can only be activated when the ride is in the aforementioned second

operative condition 101. The shot bolt actuators 110 when activated release the retaining means 111, permitting the ingress and egress of passengers.

One or more amusement rides 1 of the present invention may be linked by a computer so as to move synchronously. The rides are controlled by a supervisor and control station 120, as illustrated in Figure 10. The amusement rides can also be programmed to move
5 asynchronously to one another. The rides may also be assembled in various combinations as illustrated in Figures 11A to 11D.

The base 2 of the amusement ride 1 of the present invention can be supported on a carousel 130, as illustrated in Figure 12A. One or more of said rides can be mounted onto the
10 carousel. The carousel 130 may alternatively have an elongate centrally located column 131, from which one or more of said rides 1 may be supported, as illustrated in Figure 12B. The rides can then also rotate and move in a vertical plane simultaneously.

While specific embodiments of the invention have been shown and described in detail to illustrate the application of the principles of the invention, it will be understood that the
15 invention may be embodied otherwise without departing from such principles.